



MetaLine[®] SP1





Air consumption
380 Liters/minute
Air pressure
maximum 8,0 bars
Nozzle diameter
5 mm
Grit size specification
0,1 mm to 2 mm
Grit consumption
Up to 1,5 kg/minute
Length of grit hose
2 meters
Diameter of grit hose
9 mm
Compressed air quality
Dry & free of oil
Length of blasting gun
205 mm
Total equipment weight
800 grams
Packaging size
1 Gritblasting gun
Price (Valid from 10/21)
160,00 EUR plus VAT

Gritblasting gun for professional cleaning & roughening work

Small handhold blasting gun operated by compressed air. Designed for the effective and fast surface treatment of **local** areas. Removes corrosion & scale. Longlife characteristics due to wear resistant functional parts.



Simply place the grit hose in blasting media. By pulling the trigger the gun soaks it automatically in (vaccuum principal). Arriving at the nozzle, the air-stream will extremely speed up the grit and it will hit any surface with high speed/pressure. Use sharp contured grit to roughen surfaces. The bigger the mesh size, the **rougher** the surface will become. Use beadlike blasting medias to smoothen or polish surfaces.



Take care for all necessary safety precautions for blasting processes. Use reliable protective clothing, gloves and a full face protection. For industrial use only. Keep away from children. Never direct the gun towards human beings or animals. Air connection via European quick-couplings only. The correct working pressure has to be adjusted via a seperate air pressure regulator. Never use oxygen or flammable gases to operate the equipment. Disconnect the gun from air-supply for any cleaning or maintenance work. **Never** use sand as grit media (health danger). Lubricate the ,Ventilstift' (Pos. 6) and ,Bolzen' (Pos. 13) regularly.

1.	G401911	Überwurfmutter	2.	B040
З.	G401912	Dichtring	4.	G40
5.	G401914	Pistolenkörper	6.	G40
7.	G402032	Ventil	8.	G40
9.	G406599	Dichtring	10.	G40
11.	G406608	Verschlussschraube	12.	G40
13.	G406572	Bolzen	14.	G40
15.	G401916	Abzughebel	16.	G40
17.	G401918	Anschlußnippel	25.	G40
26.	E770117	Schraubklemme	27.	G40
28.	G401930	Gewinderohr	29.	G40
30.	G401926	Saugschlauch komp.	31.	E700

2.	B040035	Ersatzdüse
4.	G401913	Luftdüse
6.	G401915	Ventilstift
8.	G402031	Ventilfeder
10.	G406598	Verschlussschraube
12.	G406609	Luftrohr
14.	G402895	Seegerring
16.	G401917	Pistolengriff
25.	G401928	Schlauchverschraubung
27.	G401929	Materialschlauch
29.	G401931	Reduzierschraube
31.	E700013	Stecknippel R 1/4" a





P118SP-EN (October 2021)

Tel. +49 (0)7034 3100-0 | Fax +49 (0)7034 3100-5 | www.metaline.com | info@metaline.de Subject to technical modifications! Information and application examples in this document are provided to the best of our knowledge. However, they also apply without guarantee in reference to the exclusive rights of third parties and do not release the user to check the products and processes for their suitability and material tolerance regarding their intended use. We do not assume liability for the application results. Copyright by MetaLine Surface Protection GmbH, DE-71157 Hildrizhausen (1960 - 2021). MetaLine is a registered trademark of our company.

MetaLine Surface Protection GmbH | DE-71157 Hildrizhausen (Germany) | Robert-Bosch-Str. 5-11